

Goulottes de protection pvc / alu

(M = Marron, I = Ivoire, A = Gris)

Code SM-CI	Référence	Codet Enedis	L (mm)	Capacité maxi (mm ²)
P977033004	GPC 35 35	68 80 540	2,75	3 x 50 + 50 (ø 35)
P977033005	GPC 35 35 M	68 80 562	2,75	3 x 50 + 50 (ø 35)
P977033006	GPC 35 35 I	68 80 572	2,75	3 x 50 + 50 (ø 35)
P977033007	GPC 60 60	68 80 542	2,75	3 x 150 + 70 (ø 60)
P977033008	GPC 60 60 M	68 80 563	2,75	3 x 150 + 70 (ø 60)
P977033009	GPC 60 60 I	68 80 573	2,75	3 x 150 + 70 (ø 60)
P977033010	GPC 90 90	68 80 544	2,75	3 x 240 + 95 (ø 90)
P977033011	GPC 90 90 M	68 80 564	2,75	3 x 240 + 95 (ø 90)
P977033012	GPC 90 90 I	68 80 574	2,75	3 x 240 + 95 (ø 90)
P977033001	GPT 30 30	68 80 535	2,60	1 x 29 Cu (ø 16)
P977033002	GPT 30 30 M	68 80 560	2,60	1 x 29 Cu (ø 16)
P977033003	GPT 30 30 I	68 80 570	2,60	1 x 29 Cu (ø 16)
Code SM-CI	Référence	Codet Enedis	L (mm)	Dimensions (mm)
S2565012	GPT 30 30 ALU	68 80 536	2,60	30 - 30
S2565014	GPC 35 35 ALU	68 80 541	2,75	35 - 35
S2565016	GPC 60 60 ALU	68 80 543	2,75	60 - 60
S2565018	GPC 90 90 ALU	68 80 545	2,75	90 - 90
S2565020	GPC 140-50 ALU	68 80 547	2,75	140 - 50

